

5

Application

For

United States Non-Provisional Utility Patent

10

Title:

Local Emergency Alert for Cell-Phone Users

15 *Inventors:*

**DENNIS SUNGA FERNANDEZ, residing at 1175 OSBORN AVENUE,
ATHERTON, CA 94027, a citizen of the UNITED STATES;**

20 **MEGAN HU FERNANDEZ, residing at 1240 AVON STREET, BELMONT,
CA 94002, a citizen of the UNITED STATES; and**

**JARED RICHARD FERNANDEZ, residing at 1240 AVON STREET,
BELMONT, CA 94002, a citizen of the UNITED STATES.**

25

Field of Invention

Invention relates to wireless communication, particularly to mobile communications devices and services configured to provide local emergency alert.

Background of Invention

Conventional cellular phones and other wireless communication devices enable users to make emergency telephone calls for help, or to receive personal messages requesting specific mobile assistance. As more people use portable communicators, it becomes increasingly convenient, and hopefully safer, for such people to obtain emergency assistance, especially during transit. However, sometimes such conventional communication systems and methods are still inadequate to meet emergency needs, for example, when emergency facilities are distant, or when individuals are too young or sick to request assistance. Accordingly, it would be desirable to provide improved approach for emergency communication.

Summary of Invention

Invention resides in local emergency alert service and system for cell-phone or pager users. Regional or local wireless broadcast to or polling of available, voluntary, or identified communication devices operating using one or more protocol in proximate help area allows alerted users to respond to nearby emergency request or condition. Wireless communicator location is determined by relative satellite positioning, radio signal triangulation, or manual entry. Sensor may alert wireless communicator automatically of emergency condition.

Brief Description of Drawings

FIG. 1 is general system block diagram for implementing present invention.

FIG. 2 is general operational flowchart for implementing present invention.

FIG. 3 is representative alert provided to communicator user per invention.

Detailed Description of Embodiment

Communication apparatus and method are described herein for automatically facilitating local or regional emergency alert service and system for wireless communicators or devices, such as cell-phone or pager users. Regional or local wireless text, voice, video and/or data broadcast to, or polling of, available, voluntary, or identified communication devices operating in proximate help area or region according to one or more protocol allows alerted or pre-registered users to respond to nearby emergency request or condition. Wireless communicator location is determined by relative satellite positioning, radio signal triangulation, or manual position entry. Various electronic, mechanical, optical or biological sensors, such as thermometer, timer, motion detector, smoke detector, toxic gas detector, biological contamination detector, theft or intrusion alarm, etc., may alert wireless communicator automatically of emergency condition.

Generally, network server or base station accesses a memory to store or retrieve one or more representation of a communicator or device located in one or more alert region or locale. Thus, a communications controller or network processor may cause an alert message or signal to be sent to one or more communicator or device located or determined soon to be located in a certain alert region locale. Such communicator or device preferably includes a portable mobile radio transceiver for wireless voice, data, video, or other media communication, such as a cellular telephone or pager.

The communications controller or network processor may operate according to software program instructions or other hardware programmable functions to cause one or more alert message or signal to be sent or otherwise transmitted electronically in response to an alert request or similar help beacon signal received by such controller or processor from a requesting communicator or device located or determined soon to be located in the alert region or locale.

In particular, such communicator or device located in the alert region uses a locator to determining current location, such as by calculating relative global satellite positioning (i.e., GPS), radio signal triangulation, or manual textual or graphical entry of address, Cartesian coordinates or map landmark by a user. Additionally, such
5 communicator or device uses one or more electronic, mechanical, optical, or biological sensor to detect an alert or emergency condition, such as thermometer, timer, motion detector, smoke detector, toxic gas detector, biological contamination detector, theft or intrusion alarm, etc.

10 Preferably, the alert message or signal indicates a textual, audio, visual, or graphical location of a requesting communicator or device located in the alert region or locale, as well as possibly any emergency condition, update, resources, or activity. Optionally, a representation accessibly stored in communicator or device memory indicates an availability, willingness, qualification, or special emergency training of a
15 user associated with a corresponding communicator or device located or determined soon to be located in the alert region or locale.

During multi-mode operation, the communications controller or network processor may cause automatically according to software program instructions or other
20 hardware programmable functions an alert message to be sent or otherwise transmitted to a first communicator or device using one communication protocol (e.g., code-division signaling such as CDMA), and a second communicator or device using another, different communication protocol (e.g., time-division signaling such as TDMA, or frequency-division signaling such as FDMA).

25 Additionally, such controller or processor may cause the alert message or signal to be sent or otherwise transmitted using one communication protocol in response to an alert request or signal received by the controller or processor from a requesting communicator or device located or determined to be located soon in the alert region or locale using
30 another, different communication protocol.

FIG. 1 system block diagram shows apparatus embodying wireless communication network for voice, data, text, video, or other media messaging or signaling between mobile, portable communication devices 2, 8 coupled through one or more radio or cellular telephone base station 4, which may couple to digital switching network 6, such as the Internet. Base station 4 may be distributed at different geographical sites conveniently positioned for effective mobile communication with various devices 2, 8, and may include one or more wireless or network communication interface, programmable processors or controllers, as well as storage or memory for operation according to present embodiment, possibly using one or more conventional communications protocol, such as various industry-standard cellular or other wireless signaling specifications, which are hereby incorporated by reference.

Requester communicator 2 includes one or more radio frequency transmit/receive communication interface 12, detector or sensor 14, processor or controller 16, memory or storage 18, user input/output interface 20, and locator or relative positioning module 22. Similarly, other communicators 8, which may co-locate with communicator 2 in alert region 10, may include functionally-equivalent components as communicator 2. However, communicator 2 may communicate with base station 4 using a different protocol, than communicators 8 may use to communicate with base station 4.

FIG. 2 operational flowchart shows operational steps alert/ query 30, region polling 32, and messaging 34. Initially, requester communicator 2 may send an alert message or other emergency-type signal to base station 4, including location of communicator 2. This alert may be triggered automatically in real-time by one or more electronic, mechanical, optical or biological sensors coupled thereto, such as thermometer, timer, motion detector, smoke detector, toxic gas detector, biological contamination detector, theft or intrusion alarm, etc.

Alternately, such alert signal may be initiated by user on communicator interface 120 manually, for example, by entering special help request message on keyboard, or by pressing emergency alarm button.

5 Then, communications controller or network processor coupled to or included in base station 4 performs local region polling 32 to check whether any other communicators 8 are located in a common or relatively proximate geographic region or locale as requester communicator 2. This check may be accomplished automatically by computer software that checks a user registry or corresponding communicator database
10 that identifies one or more users or communicators that are available, willing, qualified, or otherwise skilled to respond to various local emergency or alert requests from other communicators.

Additionally, such automatic check may be accomplished by calculating actual
15 distance between requester communicator 2 and other candidate communicator 8 to identify which other communicators 8 are closest or within immediate vicinity to alert or request assistance. Optionally, those communicators 8 which are located in an immediately proximate area or locale (e.g., within 5-10 minutes transit time) are notified initially indicating nearby alert, while relatively further communicators 8 located in
20 neighboring proximate area or locale (e.g., next city or community) may be notified subsequently with mere advisory alert.

Communicators 2, 8 may use global positioning satellite (GPS) receiver and technique to determine actual location map coordinates, particularly at certain alert or
25 response time as determined accurately from one or more GPS satellite signal timestamp. As used herein, alert regions or locales may be predetermined areas within predefined boundaries, such as city or community limits, or dynamically defined relative to location of requester communicator 2, base station 4, or communicators 8.

Finally, such communications controller or network processor may facilitate text, voice, graphical, audio, video, or other media messaging or signaling between requester communicator 2 and one or more communicator 8 located in the alert region 10. Because communicator 2 and communicator 8 may communicate with base station 4 using
5 different protocol, it is contemplated that base station 4 may be embodied in digitally interconnected, but different wireless communication equipment for transmitting and receiving radio signals at different frequencies or coding scheme.

FIG. 3 shows representative alert 40 provided to communicator 8 user.
10 Preferably, such alert is displayed textually and graphically, possibly including vibration, sound or voice alert, to describe a current local help request, especially describing a requester property or individual condition (e.g., car or home fire or theft in progress, overheating car with live occupant, etc.). Moreover, such alert may display or otherwise communicate communicator 2 location, preferably relative to communicator 8, thus
15 facilitating local and immediate rescue or other assistance. Furthermore, such alert may report any recently updated activity associated with the particular help request.

Foregoing described embodiment of the invention is provided as illustrations and descriptions. They are not intended to limit the invention to precise form described. In
20 particular, Applicants contemplate that functional implementation of invention described herein may be implemented equivalently in hardware, software, firmware, and/or other available functional components or building blocks. Other variations and embodiments are possible in light of above teachings, and it is thus intended that the scope of invention not be limited by this Detailed Description, but rather by Claims following.